



呼び径	ゴム本体			フランジ				許容変位量				最高 使用圧力 (MPa)	試験 圧力 (MPa)								
	L	A	G	T	D	C	N-φH	偏心	伸長	圧縮	偏角										
20A	150	17	49	14	100	75	4-15	15	5	15	15°	1.6	2.4								
25A		23	61		16	125								90	4-19						
32A		37	69			18	135							100		8-19					
40A		48	86	175			140							105							
50A		63	106				175							140							
65A		76	116	185		150															
80A		100	150	210	175																
100A		124	180	250	210																
125A	150	149	209	22	280	240	8-23	25	25	1.0	1.5										
150A	200	195	260		330	290		12-23				20									
200A	150	200	320	24	400	355	12-25	25	15	25	15°	0.5	0.75								
250A	284													367	26	445	400	16-25			
300A	325													420					560	510	16-27
350A	383													471							
400A	436			519	675	620															
450A	475			569			675							620							
500A																					

⑥	充填ゴム	特殊ゴム		名称	合成ゴム製防振継手				
⑤	補強コード	合成繊維							
④	外面ゴム	合成ゴム	EPDM	型式	S-FLEX 内面フラット			JIS10K 相当	
③	内面ゴム	合成ゴム	EPDM						
②	補強リング	SWRH		作図	K.I	検図	K.I	承認	H.K
①	フランジ	SS400	ユニクロめっき	図番	12166-4		作成日	16.11.11	
記号	名称	材質	備考	AtmS 株式会社アトムズ					